



SMARTBATPLUS

SMARTBATPLUS is the senior member of the successful SMARTBAT range offering more advanced features such as WDMX wireless card, waterproof housing, grown brightness, high definition optics and fast-charge magnetic connector. It's packed in a superslim compact housing with mirror finishing useful to hide the fixture to the view of audience.



Features

- 4x12W RGBW/FullColor high-power LED delivers 1162lm
- Long lasting battery capacity: 12h color changing / 8h FULL
- Mirror finish to hide the luminaire to audience
- Protection: IP65/IP54, for temporary outdoor use
- Built-in antenna transceiver (2,4 Ghz) by Wireless Solution Sweden
- Fast charge magnetic connector
- Adjustable foot support for tilt regulation (up to 20°)



PHOTOMETRICS
AND SPECIFICATIONS
WWW.MUSICLIGHTS.IT





 3,6 kg

LIGHT SOURCE

- Source: 4x12W RGBW LEDs
- Luminous Flux: 1162lm
- Lux: 2064lux @3m
- Source Life Expectancy: >50.000 h

OPTICS

- Beam Angle: 11°
- Field Angle: 19°

COLOR SYSTEM

- Color Mixing: RGBW/FC
- White Presets: 3200-9000K
- Color Wheel: Virtual color wheel with presets
- Macros: Built-in white presets

DYNAMIC EFFECTS

- Static Color Mode: Selection of static color
- Manual Color Mode: Manual adjustment of color
- Auto Mode: Built-in programs with execution speed adjustment

BODY

- Tilt Angle: Adjustable foot support for tilt regulation (up to 20°)
- Body: Sturdy die-cast aluminium body conceived for long-time durability
- Body Color: Mirror finishing

CONTROL

- Protocols: DMX
- Dmx Channels: 3/4/6/10ch
- W-DMX: Built-in Wifi receiver with WDBOX protocol
- Display: Black OLED touch display
- Firmware Upgrade: Yes, via USB-DMX interface (UPBOX1) not included
- IR: Infra-Red sensor controlled by remote

ELECTRONICS

- Dimmer: Linear 0~100% electronic dimmer
- Dimmer Curves: 4 Different dimming curves available
- Strobe/Shutter: 1-25 flash/s, electronic
- Operating Temperature: 0/35°
- Flicker: Flicker free operation

ELECTRICAL

- Power Supply: 100-240V – 50/60Hz

BATTERY

- Battery: 16,8V Lithium
- Autonomy (color change mode): 12h
- Autonomy (permanent white full-on): 8h
- Recharge Connection: Magnetic fast-charge in case
- Recharge Time: 4h/max
- Battery Status: Shown on Display

PHYSICAL

- IP: IP65 (front) - IP54 (bottom)
- Cooling: Natural cooling of the peculiar chassis and to absence of fans
- Suspension And Fixing: M12 threaded insert for easy clamp installation and a Kensington lock position
- Dimensions (WxHxD): 138x145x202mm
- Weight: 3,6Kg



Adjustable foot support for tilt regulation (up to 20°)

Optional Accessories

FCLSMARTBATPLUSE: Flight-case designed to contain 6pcs SMARTBATPLUS